

Revolution Oil

A New Generation of Lubricants

Revolution Oil Limited
Dagnall Road
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999
Fax: +44 (0) 1442 842777

www.revolutionoil.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No.GB 815 3964 16

Technical Data Sheet

20W Monograde Plant Oil



20W Monograde Plant Oil

Universal Oils

Description

Monograde Plant Oil 20W is a superior quality engine lubricant. The combination of solvent refined base oils and high technology additives is designed to give maximum protection to engines working under moderate or severe conditions.

Application

This oil may be used in a variety of turbocharged or naturally aspirated engines. It is also suitable for general plant equipment, transmissions, torque converters and hydraulic systems. Refer to the manufacturers handbook.

Benefits

- excellent high temperature stability
- improved bore polishing protection
- reduced engine wear
- excellent sludge control

Performance Level

- API CE/SG
- MIL-L-46152B
- MIL-L-2140D
- CCMC D4
- MB 227.0 & 227.1
- MACK EO-K
- MAN 270 & 271
- CATERPILLAR TO-2
- ALLISON C3

Typical Test Data

| | Units | Inspection Data |
|---------------------------|--------------------|-----------------|
| Specific Gravity 15°C | Kg/m ³ | 0.883 |
| Kinematic Viscosity 100°C | mm ² /s | 8.19 |
| Kinematic Viscosity 40°C | mm ² /s | 59.02 |
| Viscosity Index | | 107 |
| Total Base Number | mg KOH/mg | 9.14 |
| Pour Point °C | | -30 |
| Flash Point °C | | 220 |

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.