

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Two Stroke Engine Oil

Two Stroke Engine Oil

Two Stroke Oils

Description

Revolution Two Stroke is a high quality, low ash two stroke oil. It has been specially formulated from the latest additive technology and base oil components to produce a low smoke, clean burning product. It is designed to exceed the performance requirements of API TC and is suitable for both premix and injector systems.

Benefits

- Protects against piston and cylinder scuffing
- Superior levels of anti-wear protection
- High lubricating film strength
- Greatly reduced deposit formation

Applications

Revolution Two Stroke is suitable for use in motorcycles of low to medium output and can be used in a variety of two stroke applications such as chainsaws, hedge cutters, go karts, lawnmowers and snowmobiles. Always refer to the equipment handbook for mixing ratios and specification requirements.

Performance Level

API TC

ISO-EGB (JASO FB)

Typical Inspection Data

Specific Gravity @ 15.6 degrees centigrade	0.880
Kinematic Viscosity @ 100 degrees centigrade	8.94
Flash Point degrees centigrade	170
Appearance	Red

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.